

Respirator Type	Continuous flow airline respirator for use with high pressure compressed air or ambient air pumps
Components	<ul style="list-style-type: none">• Respirator Helmet and Cape• Breathing Tube with Fitting or Optional Climate Control Devices• Air Supply Hose
Approvals	<ul style="list-style-type: none">• NIOSH Approved Type C and CE, Continuous Flow Class• ANSI/ISEA Z89.1 – 2014 (R 2019), Type I, Class C Head Protection• ANSI/ISEA Z87.1 – 2020, Z87+ High-Impact Face Protection• 1,000 APF with Third Party Certification Testing
Specific Features	<ul style="list-style-type: none">• For high pressure compressed air, Bullard has products for air filtration and CO monitoring of this type of compressed supply air• Assembled in the USA
Helmet	<ul style="list-style-type: none">• Removable and launderable comfort padding kit• Available in 4 distinct colors: Modern Navy, Vintage Yellow, Imperial Red, Bullard Green• Weight: 2.6 pounds (helmet, suspension, lenses and cheek pads)• No OSHA fit testing required to use the GVX respirator system.• Center mounted breathing tube connection to helmet• Lightweight adjustable 6-pt. Flex-Gear® ratchet suspension with 1" wide webbing, fits sizes 6.5" - 8"• Replaceable breathing tube connection on the GVX helmet• "Grit Guard" visor to prevent debris in-between lenses• Removable, adjustable cheek pads for increased stability• Non-porous shell allows for easy cleaning• Replaceable Inner lens made out of Tritan™ .040" thick PETG polymer• Viewable area of approx. 9.75" wide x 4" tall• Replaceable outer lens available in .015" or .040" thick PETG polymer• Optional adhesive-backed Mylar® Lens Covers• Tinted lenses available in green or smoke color• Optional Tear Off Lens Covers
Capes	<ul style="list-style-type: none">• Double lining above the neck for additional durability and protection• Sewn in knitted neck cuff provides snug, comfortable protection barrier to airborne contaminants while helping maintain positive pressure within the helmet• 5 Nylon cape styles available in 28" and 38" length with over the shoulder and cut-off cap sleeves• Made from 8 oz. Nylon Denier• Full length Hibernian parka available in 38" length with long sleeves• Seal type on cape to helmet is a continuous steel cable• Industrial or machine washable
Climate Control	<ul style="list-style-type: none">• Optional climate control assembly (HC2400) available to cool or warm incoming air up to 30 degrees. (High Pressure Compressed Air Only)• Cool Tubes capable of supplying cooler air to the worker. High Pressure Compressed Air (AC1000) gives up to 30 degrees of cooling (High Pressure Compressed Air Only)• Low Pressure Air, supplied by Ambient Air Pump, (Frigitron 2000) gives up to 20 degrees of cooling• Cool tube constructed of metal and molded plastic for increased durability• Cool Vest (DC70) available using a DC5040 Cool Tube and the same airline. Available in two sizes – medium/large or XL/XXL. (High Pressure Compressed Air Only)





GVX Series Abrasive Blasting Respirator Tech Specifications

Breathing Tube Assembly with Flow Control Device

- Available with constant flow control device with 1/2" Industrial Interchange (Hansen compatible) quick disconnect coupler for ambient air pumps
- Available with constant flow control device with 1/4" quick disconnect coupler for compressed air
 - Industrial Interchange (Hansen Compatible) in steel, brass or stainless steel
 - Snap-Tite in steel, brass or stainless steel
 - Schrader in steel
 - CEJN in steel
 - Bayonet in steel

Airline Supply Hose

- Approved for use with 25-300 feet of airline supply hose depending on your configuration for compressed air
- Approved for use with 50-300 feet of airline supply hose for ambient air pumps
- Choice of EPDM-reinforced rubber 3/8" I.D. hose for compressed air or 1/2" I.D. hose for ambient air pumps
- Offers 1/2" industrial interchange (Hansen compatible) nipple for ambient air pumps
- Offers 1/4" approved quick disconnect couplers compatible with breathing tube fittings for compressed air
 - Industrial Interchange (Hansen Compatible) in steel, brass or stainless steel
 - Snap-Tite in steel, brass or stainless steel
 - Schrader in steel
 - CEJN in steel
 - Bayonet in steel

Warranty

2-year full warranty that the GVX helmet will be free of defects in material and workmanship under normal use and service as a blast helmet. Capes, breathing tubes, and other disposable accessories not included. See the GVX Series Respirator User Manual for complete details.

Bullard Center

2421 Fortune Drive
Lexington, KY 40509 • USA
877-BULLARD (285-5273)
Tel: +1-859-234-6616
Fax: +1-859-246-0243

Americas Operations

1898 Safety Way
Cynthiana, KY 41031 • USA
877-BULLARD (285-5273)
Tel: +1-859-234-6616
Fax: +1-859-234-8987

Bullard GmbH

Dieselstrasse 8a
53424 Remagen • Germany
Tel: +49-2642 999980
Fax: +49-2642 9999829

Bullard Asia Pacific Pte. Ltd.

51 Changi Business Park Central 2
#03-04 The Signature
Singapore 486066
Tel: +65 6745 0556



©2023 Bullard. All rights reserved.
Flex-Gear and Free-Air
are registered trademarks of Bullard.
Tritan is a trademark of Eastman.
Mylar is a registered trademark of Dupont
Teijin Films.
6081009497A (0823)