

## Specifications

- Capacity to supply one NIOSH-approved respirator
- Portable – Includes roll cage and wheel kit (standard)
- Oil-less\* – does not produce CO, eliminates need for temperature alarms, and associated airline filters
  - \* Compressor does contain lubricated motor bearings and rod bearings. The bearings are a sealed design and lubricated for the life of the product. They are also located outside the compressed air path of the compressor, eliminating any potential lubrication leakage inside the air path.
- 2.0 HP, electric-driven
- 6 ft. 115 AC V cord with NEMA 5-20 amp three-pronged plug
- Liquid-filled pressure gauge (0-100 psig)
- 1/2" Industrial Interchange (Hansen compatible) quick-disconnect coupler
  - ICE Pump MUST be connected to a minimum length of 100' of 1/2" ID air supply hose
- Weight: 100 lbs. (45.4 kg)  
Shipping weight: 185 lbs. (83.9 kg)
- Sound Level (dBA) at:
  - 1 ft. – 96.4
  - 6 ft. – 88.8
  - 10 ft. – 84.6
  - 15 ft. – 80.6
- Air flow of 8 cfm at 60 psig (225 lpm @ 4 bar)
- Dimensions: 28" L x 18" W X 20.5" H  
Shipping Dimensions: 48" L x 32" W X 35.5" H
- Maximum Outlet Air pressure of 60 psig (4 bar)
- Does not need to be bolted down
- No calibration required
- Assembled in the USA



## Electrical Motor Specifications

- Open, drip-proof enclosure
- Meets UL requirements
- CSA approved
- 2.0 HP
- Single Phase
- 60 Hz cycle
- 115 / 230 AC volts
- 20 Amps @ 115V / 10 Amps @ 230V
- 1.15 Service Factor
- Internal Thermal Overload

## Filters

- Air inlets (4) can be located up to 300 feet away from pump. Inlet filters must be located in a clean air environment containing a continuous supply of at least Grade D breathable air, at all times.
- Medium Efficiency Inlet Filters (particulates filtered out of ambient air supply that can cause premature wear and tear on rotor/vanes of pump). Replace after 500 operational hours or less depending on working conditions
- 90-micron Inline Outlet Strainer. Replace after 500 operational hours or less depending on working conditions

## Respirator Capabilities

- May be used in conjunction with any manufacturer's NIOSH-approved supplied air respirators. Check the respirator's user manual to verify correct pressure and CFM requirements.

## Warranty

- 1-year limited warranty to original purchaser from date of purchase

**Bullard Center**  
2421 Fortune Drive  
Lexington, KY 40509 • USA  
877-BULLARD (285-5273)  
Tel: +1-859-234-6616  
Fax: +1-859-246-0243

**Americas Operations**  
1898 Safety Way  
Cynthiana, KY 41031 • USA  
877-BULLARD (285-5273)  
Tel: +1-859-234-6616  
Fax: +1-859-234-8987

**Bullard GmbH**  
Dieselstrasse 8a  
53424 Remagen • Germany  
Tel: +49-2642 999980  
Fax: +49-2642 9999829

**Bullard Asia Pacific Pte. Ltd.**  
51 Changi Business Park  
Central 2  
#03-04 The Signature  
Singapore 486066  
Tel: +65 6745 0556



©2024 Bullard. All rights reserved.