



20LF Series Loose-Fitting Facepieces Technical Specifications

Respirator Type Supplied Air Respirators (SAR) or Powered Air Purifying Respirators (PAPR)

Respirator

Approvals

- 25 APF (Assigned Protection Factor) for NIOSH Approved EVA/EVAHL PAPR Respirators with 20LF Series Loose-Fitting Facepieces
- 25 APF (Assigned Protection Factor) for NIOSH Approved Supplied Air Respirator System

20LF Series Loose-Fitting Facepiece

- Sewn-in suspension
- Latex-free
- Quick-attach twist lock connection color coded to indicate facepiece size
- No fit test required
- Accommodates beards, hearing protection, prescription eyewear or safety glasses
- Made out of Dupont Tychem® 2000
- Chemically resistant PETG lens
- Soft plenum over-the-top air delivery system

Breathing Tube Assembly

- Approved and available in 3 different lengths
- Approved and available with constant or climate control device with 1/2" Industrial Interchange (Hansen compatible) quick disconnect coupler for ambient air pumps.
- Approved and available with constant or climate control device with 1/4" quick disconnect coupler for high pressure supplied air with the following choices of fittings:
 - Industrial Interchange (Hansen Compatible) in steel, brass or stainless steel
 - Snap-Tite in steel, brass or stainless steel
 - Schrader
 - CEJN
 - Bayonet
- Standard Nylon belt or optional Decontamination belt
- Available with 3 different breathing tube covers made of Tychem® 2000 (QC), Tychem® 4000 (SL) or clear LDPE

Airline Supply Hose

- Bullard V-10 airlines (3/8" ID) are approved for use with 25 ft. to 300 ft. of airline supply hose(s) using compressed supplied air systems.
- Bullard V-20 airlines (1/2" ID) are approved for use with 50 ft. to 300 ft. of airline supply hose(s) using ambient air / free air systems.
- Bullard airline hoses are made of EDPM reinforced rubber hose manufactured for supplied air respirator systems
- Each Bullard V-20 airline hose (1/2" ID) is supplied with Industrial Interchange (Hansen Compatible) QD female Coupler and QD male nipple for use with ambient air / free air systems.
- Each Bullard V-10 airline hose (3/8" ID) is supplied with a choice of various 1/4" QD airline fittings for use with compressed supplied air systems.
 - Industrial Interchange (Hansen Compatible) in steel, brass or stainless steel
 - Snap-Tite in steel, brass or stainless steel
 - Schrader
 - CEJN
 - Bayonet



20LF Series Loose-Fitting Facepieces Technical Specifications

Optional Climate Control

- Cool tube (AC1000) – High Pressure Supplied Air only
 - Cools incoming air by as much as 30°F (17°C)
 - Adjustable airflow control valve for individual comfort
- Hot/Cold Tube (HC2400) – High Pressure Supplied Air only
 - Cools or warms incoming air by as much as 30°F (17°C)
 - Adjustable airflow control valve for individual comfort
 - Change between cooled or warmed air in seconds
- Dual-Cool (DC5040) – High Pressure Supplied Air only
 - Cools incoming air by as much as 30°F (17°C).
 - Cools air supplied to both hood and cooling vest
 - Separate control knobs allow adjustment of the temperature of air to each zone
 - High Pressure Supplied Air sent to the DC5040 must have the capacity to supply a minimum of 30 cfm (850 lpm) of air flow
- Cooling Vest (DC70)
 - Sizes M, L, XL, XXL

Warranty

- 1 year limited manufacturer warranty for original purchaser from date of purchase.

Bullard Center
2421 Fortune Drive
Lexington, KY 40509 • USA
877-BULLARD (285-5273)
Tel: +1-859-234-6616
Fax: +1-859-246-0243

Americas Operations
1898 Safety Way
Cynthiana, KY 41031 • USA
877-BULLARD (285-5273)
Tel: +1-859-234-6616
Fax: +1-859-234-8987

Bullard GmbH
Dieselstrasse 8a
53424 Remagen • Germany
Tel: +49-2642 999980
Fax: +49-2642 9999829

Bullard Asia Pacific Pte. Ltd.
51 Changi Business Park
Central 2
#03-04 The Signature
Singapore 486066
Tel: +65 6745 0556



©2024 Bullard. All rights reserved.