



PX Series Structural Fire Helmet Technical Specifications

Helmets for Structural Firefighting shall meet or exceed NFPA 1971, Standard on Protective Ensembles for Structural Fire Fighting and Proximity Fire Fighting, (Pertaining to Structural Fire Helmets). Certification/verification shall be furnished by written documentation supplied by a recognized independent third party test laboratory.

A sample helmet meeting the requirements of this specification shall be supplied upon request for inspection and verification of compliance within 10 working days.

The authority having jurisdiction reserves the right to accept bids submitted per their evaluation based upon compliance to the standard performance and any other applicable requirements concerning fit and function.

The authority having jurisdiction reserves the right to accept the most appropriate helmet based on the above stated criteria without regard to lowest price offerings.

Successful bidders shall ship helmets per award from the manufacturer within 14 working days after receipt of order from the distributor.

General

Helmets conforming to this specification are designed to help protect the firefighter from head and neck injuries related to structural firefighting activities.

The helmet manufacturer shall be certified ISO 9001 company to assure quality procedures and production capabilities.

Physical Configuration

The basic helmet shall be flared, rear-brim design with a length of 14", a width of 10" at the faceshield hardware and a height of 6-7/8".

Shell

The helmet shell shall be of contemporary style and shall be constructed of heat-resistant thermoplastic. Color pigment shall be added to the thermoplastic resin as part of the manufacturing process that molds the helmet to help maintain appearance by masking chips and scratches that might occur in daily wear and tear. The shell finish shall be available in white, yellow, red, black, orange, lime-yellow, and blue. The edge of the outer shell shall have aluminum reinforced, elastomeric edge beading that is secured at the rear of the brim by a stainless steel clip and D-ring fastened by a stainless steel rivet. The edge beading shall not melt, drip or ignite when tested to NFPA 1971 Section 8.6 Heat Resistance requirement.

Impact Liner System

The impact liner shall consist of a urethane foam liner glued to a black high-heat resistant inner shell with a heat deflection temperature > 220° F @ 264 psi. The urethane foam liner shall be formed without the use of CFCs to eliminate the potential for additional expansion when subjected to heat during actual use.

The black inner shell shall have four 1" x 3" pieces of adhesive-backed hook material attached, two to each side, to secure the ear/neck protector at the sides of the inner shell.

Crown Strap Suspension System

The crown strap suspension system shall be three 3/4" nylon web straps attached to six nylon keys. The keys shall be locked into the lip of the inner shell against the urethane impact liner.

Ratchet Headband

The helmet shall have a quick-adjustment sizing capability by means of a ratchet adjustment system attached to a heat-resistant nylon headband. The headband shall be attached to the inner shell by four black acetal buttons (two front, two rear). The headband shall have the ability to be raised or lowered inside of the inner shell by location points on the headband. This adjustment shall not affect the height of the helmet on the firefighter's head.

The ratchet portion of the headband shall have a ratchet height adjuster located at the rear of the headband, inside of the inner shell, to permit the ratchet to be positioned for comfort on the nape of the firefighter's head. This ratchet height adjuster shall permit at least 1" of travel by means of three height adjustment keys for proper fit. This independent adjustment component shall have a 3/4" piece of adhesive-backed Velcro hook material attached at the center rear of this component to secure the rear portion of the ear/neck protector.

Brow Pad

The headband shall be supplied with a fire retardant (FR) cotton brow pad sewn around the perimeter, backed with foam cushion padding material at the forehead, that is removable for laundering and replacement. Attachment to the headband with stitching will not be permitted. A leather brow pad option must be available.





Chinstrap

The chinstrap shall be two pieces of 3/4" black Nomex® webbing with a super tough nylon quick release buckle and a chrome-plated postman's slide fastener.

The male side of the quick-release buckle shall be anchored to the right side of the outer shell with a dielectric anchor block secured bracket with two stainless steel screws, or for ReTrak Series chinstraps, with three stainless steel screws. The long portion of the chinstrap with the female side of the quick-release buckle and the postman's slide fastener shall be attached to the left side of the outer shell in the same manner.

When the chinstrap is connected and fully extended, maximum length shall be at least 24" when measured from one anchor block to the opposite anchor block.

Ear/Neck Protector

The ear/neck protector shall consist of a 6 oz. rip-stop Nomex outer shell backed with three layers of FR cotton flannel for comfort and protection. A 1" strip of loop material shall be stitched in one continuous band across the top of the outer shell of the ear/neck protector for attachment to the inner shell.

When properly attached to the inner shell of the helmet, the ear/neck protector shall have the following minimum coverage to the sides and rear of the helmet brim:

1. 6" from the sides of the helmet brim at the chinstrap.
2. 6-1/2" from the center rear of the helmet brim.

Eye Protection

Faceshield

The faceshield shall be a hard-coated PPC material 4" x 15" that is molded in the formed position and designed to fit the contour of the helmet brim. The faceshield shall be certified to meet the optic requirements of ANSI/ISEA Z87.1, Standard for Eye and Face Protection. This certification shall meet NFPA 1971 requirements for heat and impact performance.

When mounted, the faceshield shall permit a minimum retractability of 90° in the stowed position.

The faceshield shall be mounted to the brim of the outer shell by a glass-reinforced, flame resistant, nylon handwheel/stainless steel threaded stud attached to a brass T-nut which is supported by an aluminum washer and mounting bracket. The faceshield hardware shall meet the NFPA 1971 Flame Resistance Test. The mounting bracket shall be secured to the brim of the outer shell by the chinstrap screws.

ReTrak™ Visor

The visor, when not deployed, shall store in a protected fashion between the inner liner and the outer shell. The visor shield shall meet the requirements of ANSI/ISEA Z87.1, Standard for Eye and Face Protection. This certification shall meet NFPA 1971 requirements for heat and impact performance. The visor material shall be a high heat polyarylate. A nose comfort pad shall be provided. The visor shall be optically correct with a scratch resistant coating on the inner and outer surfaces.

The visor shall be deployable by the wearer with a single hand. The visor shall transverse across two axes of movement to accommodate most eye glasses, safety glasses, or other protective eyewear.

No tools shall be required for the wearer to remove the eye shield for cleaning, decontamination, or replacement. Visor must be held in place by clips. Clips must be able to be actuated with the use of a single finger.

Goggles

The goggle shall be full-perimeter filtered ventilated around the dark-gray molded frame. The lens shall be 2.8mm polycarbonate with anti-fog and anti-scratch coatings. The goggle shall be certified to meet the optic requirements of ANSI/ISEA Z87.1, Standard for Eye and Face Protection. The goggle strap system shall include a quick adjustment for length/tension that can be used while wearing firefighter gloves. The goggle shall be retained by either a direct connection of two goggle straps that attach to the left and right sides of the inner shell system, or via a full goggle strap that fit around the outer shell

Retro-reflective Trim

The outer shell shall have 8 pentagon-shaped, fluorescent lime-yellow, retro-reflective markings equidistantly located around the circumference of the dome. The reflective materials shall be glass bead based to maximize the resistance to heat exposure experienced in firefighting. Options of colors must include lime-yellow and red orange (standard) as well as optional trim in lime-yellow and red-orange and maple leaf.

TrakLite®

Helmet shall be made available with optional integrated light. Full product specifications of integrated light can be found on our website: <https://www.bullard.com/product/traklite>

Warranty

Bullard warrants to the original purchaser that the firefighter helmet and non-electronic components are free of defects in materials and workmanship under normal use and service for a period of five (5) years from the date of manufacture on the helmet shell and lifetime (as defined in NFPA 1851: 10 years) warranty on the non-electronic components.

Bullard Center

2421 Fortune Drive
Lexington, KY 40509 • USA
877-BULLARD (285-5273)
Tel: +1-859-234-6616
Fax: +1-859-246-0243

Americas Operations

1898 Safety Way
Cynthiana, KY 41031 • USA
877-BULLARD (285-5273)
Tel: +1-859-234-6616
Fax: +1-859-234-8987

Bullard GmbH

Dieselstrasse 8a
53424 Remagen • Germany
Tel: +49-2642 999980
Fax: +49-2642 9999829

Bullard Asia Pacific Pte. Ltd.

51 Changi Business Park
Central 2
#03-04 The Signature
Singapore 486066
Tel: +65 6745 0556



©2023 Bullard.
All rights reserved.
Nomex is a registered trademark of the
E.I. DuPont de Nemours & Company.
Velcro is a registered trademark of
Velcro USA.

8229 (0823)