

# salus HC

A battery-powered, positive pressure powered air-purifying respirator (PAPR).

Designed to the PAPR100-P NIOSH standard specifically for healthcare, but is suitable for many applications including laboratory, pharmaceutical and emergency response.

- Worn on the shoulders with a flexible, closed cell carriage to evenly distribute the weight over the wearer's center of gravity.
- Quick connect breathing tube connections and an accordion style breathing tube with a maximum stretch of 15-in.
- Includes a single power button with ON/OFF and two (2) speeds conveniently located on the chest.



## Individual System Components

- NIOSH approved for use with Bullard LF-Series hoods.
- Individual components for SALUS HC system include a HEPA filter, breathing tube, LF-Series hood, battery and battery chargers.
- Required components: SALUS HC assembly and LF-Series hood.

## Battery & Charger

High-capacity, rechargeable Lithium Ion (Li-Ion)

Battery charge status on product: 10-25%, 26-50%, 51-75%, 76-100%

Delivery status battery capacity: 30%

7.5V nominal, 6300 mAh, 8.7V Peak; 3.2A charge/discharge

Battery runtime: 4 to 6 hours (varies based on hood model and airflow setting)

Battery recharge: < 2 hours

Single-port battery charger

AC Adaptor charger: Input 100 – 240V, 50/60Hz, output 13.5Vdc ±5%, 24W

Battery charger dimensions: 120 x 64 x 43mm (4.7 x 2.5 x 1.7-inch)

## Blower & Carriage

Number of speeds: 2 (high/low)

Airflow (low): 200 L/min (6.5 CFM)

Airflow (high): 215 L/min (7.5 CFM)

Brushless DC motor rated for 40,000+ hours

Bullard Active Flow Technology™

Closed cell PAPR carriage: chemically resistant, waterproof, UV resistant, antiallergic, antimicrobial

Universal size

Includes user-adjustable, TPU coated straps

## Respirator Hood

Fabric material: Dupont™ Tychem® QC 2000

Lens material: PETG

Assigned protection factor (APF): 25

Suspension: Sewn-in, soft suspension

Model sizes: 9 variations to accommodate virtually all face and head sizes –

20LF - 3 sizes

20LF2 - 3 sizes

20LF HEPA - 3 sizes



SAFETY. SINCE 1898.™

# salus HC

## Country of Origin

Made in Kentucky, USA with locally and globally sourced components

## Approvals

SALUS HC: NIOSH (PAPR100-P)  
Bullard: ISO 9001:2015

## Filter

Type: High Efficiency Particulate Air (HEPA)

Filtration: 99.97% of dust, pollen, mold, bacteria, and any airborne particles with a size of 0.3 microns (µm)

## Breathing Tube

PVC coated with quick-connect and twist-lock connections

Resting length: 7.5-inch

Stretch length: 15-inch

## Safety Systems

Built-in low flow alarm verification

Low airflow: 170 L/min (6 CFM)

Low battery alarm activation: 5%

## Operating Conditions

Operating temperature:  
32° F to 104° F (0° C to 40° C)

## Total Weight

No breathing tube or hood - 3lbs

No breathing tube, hood, or battery - 2.6lbs

## Storage Conditions\*\*

Relative humidity: < 90%

Temperature (daily storage):  
-22 °F to 122 °F (-30 °C to 50 °C)

Temperature (extended storage):  
40 °F to 95 °F (4 °C to 35 °C)

Optimal storage temp for battery to maintain charge while off charger: 60 °F (15 °C)

## Shelf life\*

Battery: 1 year

Filter: 10 years

Hood: 5 years

Packaging to withstand high vertical force for long-term stock piling

## Latex

SALUS HC assembly does not contain components of dry or natural rubber latex

## Decontamination

See SALUS HC User Manual for details  
[www.bullard.com/salushc/usermanual](http://www.bullard.com/salushc/usermanual)



## Warranty

Blower: 2 years\*\*\*

Battery & charger: 1 year

Breathing tube: 1 year

Filter: 1 year (unopened in original packaging)

Hood: 1 year (unopened in original packaging)

## Training

[www.bullard.com/salushc/getstarted](http://www.bullard.com/salushc/getstarted)

\* From the original date of manufacture when stored in original packaging and recommended storage conditions.

\*\* Store the battery with a state of charge between 40-60%

\*\*\* Standard warranty of 1 year. Requires product registration at [www.bullard.com/salushc/getstarted](http://www.bullard.com/salushc/getstarted)

**Bullard Center**  
2421 Fortune Drive  
Lexington, KY 40509 • USA  
877-BULLARD (285-5273)  
Tel: +1-859-234-6616  
Fax: +1-859-246-0243

**Americas Operations**  
1898 Safety Way  
Cynthiana, KY 41031 • USA  
877-BULLARD (285-5273)  
Tel: +1-859-234-6616  
Fax: +1-859-234-8987

**Bullard GmbH**  
Dieselstrasse 8a  
53424 Remagen • Germany  
Tel: +49-2642 999980  
Fax: +49-2642 9999829

**Bullard Asia Pacific Pte. Ltd.**  
51 Changi Business Park  
Central 2  
#03-04 The Signature  
Singapore 486066  
Tel: +65 6745 0556



**SAFETY. SINCE 1898.™**